

West Deer Model	size	Lumens (Delivered)	Efficacy (lm/w)	Input power (watt)	current (ma)	LED life L70 (hours)
WD-P2-18W-ADS-30K	1x1	1500	83	18	450	50000
WD-P2-18W-ADS-35K	1x1	1600	88	18	450	50000
WD-P2-18W-ADS-40K	1x1	1760	98	18	450	50000
WD-P2-18W-ADS-42K	1x1	1760	98	18	450	50000
WD-P2-18W-ADS-57K	1x1	1800	100	18	450	50000
WD-P1-40W-CDS-30K	1x4	3800	95	40	1100	50000
WD-P1-40W-CDS-35K	1x4	3900	97.5	40	1100	50000
WD-P1-40W-CDS-40K	1x4	4000	100	40	1100	50000
WD-P1-40W-CDS-42K	1x4	4000	100	40	1100	50000
WD-P1-40W-CDS-57K	1x4	4080	102	40	1100	50000
WD-P4-40W-CDS-30K	2x2	3800	95	40	1100	50000
WD-P4-40W-CDS-35K	2x2	3900	97.5	40	1100	50000
WD-P4-40W-CDS-40K	2x2	4000	100	40	1100	50000
WD-P4-40W-CDS-42K	2x2	4000	100	40	1100	50000
WD-P4-40W-CDS-57K	2x2	4080	102	40	1100	50000
WD-P7-75W-CDS-30K	2x4	7300	97	75	2140	50000
WD-P7-75W-CDS-35K	2x4	7400	98	75	2140	50000
WD-P7-75W-CDS-40K	2x4	7500	100	75	2140	50000
WD-P7-75W-CDS-42K	2x4	7500	100	75	2140	50000
WD-P7-75W-CDS-57K	2x4	7650	102	75	2140	50000