

PROJECT: _____
TYPE: _____
PRODUCT: _____
APPROVED BY: _____

PRODUCT FEATURES

- Intended for vandal-prone applications including Public Areas, Corridors, Stairways, Parking Garages, Restrooms, Lobbies, Schools, and more.
- Available in three color temperatures - 3500k, 4000k, and 5000k
- This product is Made in America and complies with the Buy American Act requirements



NWLUD

ORDERING INFORMATION

Example: NWLUD-35-UN-BK



NWLUD				
Series	Lamp Type 35 = 3500°K 40 = 4000°K 50 = 5000°K	Voltage 12 = 120V 27 = 277V UN = Universal (120V-277V)	Finish BK = Black WH = White	Options EML = Emergency Battery (remote)* TH = Torx® Head Fasteners *Cannot use with UN voltage

SPECIFICATIONS

HOUSING: Die cast, one-piece marine grade aluminum.

LENS: UV stabilized white opal polycarbonate.

LED: Available in three color temperatures 3500°K, 4000°K and 5000°K. 14.4W on 3 LED modules with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 80 CRI standard. Minimum 60,000h with 85% of lumen maintenance in 25°C ambient temperature, per IES TM-21 testing report.

REFLECTOR: 40" thick white aluminum for high reflectivity serves as heat sink and unitized with electrical components.

FASTENERS: Stainless steel Phillips fastners.

FINISH: Durable polyester powder coat finish in black or white.

GASKET: An injection molded, continuous piece silicone rubber gasket to prevent infiltration.

MOUNTING: Surface wall mount installation.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratories.



The Ludo Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal Resistant achirtectural luminaires when installed according to our instructions for the life of the original installation if the fixture should faile due to physical abuse.*

*Exclusions to the New Star Promise are gunfire and chemical reactions

DIMENSIONAL DATA

