

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



CCEX Series

PRODUCT FEATURES

- Intended for Commercial applications such as offices, medical office buildings, corridors, lobbies, waiting rooms, and more
- Canopy for Top or End Mount. Universal knockout on back plate for Wall Mount
- Field-selectable Red, Green or Red/Green legend. Universal Single/Double face
- Fixture is certified to UL standards for Damp Locations, UL924, NFPA101 Life Safety Code, NEC, OSHA, Certified to CEC under Title 20 Regulations
- This product is Assembled in America and complies with Buy American Act requirements when specified.

ORDERING INFORMATION

Example: CCEX-UF-RW-WH-EM



CCEX	UF				
Series	Face UF = Universal Single/Double Face	Lettering RW = Red Letters GW = Green Letters RGW = Red/Green Letters	Housing Color WH = White BK = Black	Battery Blank = AC-Only EM = Emergency Battery	Options CUS = Custom Signage* SDT = Self-Diagnostics** BAA = Buy American Act compliant *Consult factory **Available only with EM units. Not available with RGW units



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

CONSTRUCTION: Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant thermoplastic. Aesthetically pleasing, curved face, rounded corner design. Snap-out chevron directional indicators.

ELECTRICAL: Dual 120V/277V standard. Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours. 1.2V long life, maintenance-free, rechargeable NiCd battery (EM models only).

FASTENERS: Stainless steel Philips fasteners.

INSTALLATION: Canopy for Top or End Mount. Universal knockout on back plate for Wall Mount.

WARRANTY: Limited five (5) year warranty.

LABEL: Fixture is certified to UL standards for Damp Locations, UL924, NFPA101 Life Safety Code, NEC, OSHA, Certified to CEC under Title 20 Regulations. This product is Assembled in America and complies with Buy American Act requirements when specified.

DIMENSIONAL DATA

