

STARCLEAN AERFLO™ TEARDROP AMBER SERIES

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Aerodynamic design ideal for laminar flow environments. Intended for Cleanrooms, Vivariums, Containment Areas, Hospitals, Laboratories, Pharmaceuticals, and more
- Available in 2ft, 4ft, and 8ft lengths
- Certified IP53 per IEC60598 Meets ISO3/Class 1 Cleanroom Standards, NSF2 Splash Zone/Non-Food Zone, Optional MIL-STD-461G
- This product is Made in America and complies with the Buy American Act (BAA) and the Build America, Buy American Act (BABAA).



AFO Amber Series

ORDERING INFORMATION

Example: AFO4-STLA-90C-UN



AFO		ST	LA			
Series	Size	Lumen Output	Color Temp.	CRI	Voltage	Options
	2 = 2ft 4 = 4ft 8 = 8ft *Nominal size. Dimensional data on Page 2.	ST = Standard	LA = Amber LED (570nm)	80C = 80 CRI 90C = 90 CRI	12 = 120V 27 = 277V UN = Universal (120V-277V)	EL = Emergency Battery Pack* FZ1 = Fuse (120V) FZ2 = Fuse (277V) RW = Row Mount** TK = T-bar installation Kit MS = MIL-STD-461G *If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity. Not available in 2ft size. **Joiner hardware supplied.



New Star Lighting
 2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

Housing: Die-formed aluminum housing, seam-welded and ground smooth.

LENS: Opal acrylic lens balances diffusion and light transmission.

LED: High output Amber LEDs (570nm) with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.



ELECTRICAL: 120-277VAC 50/60Hz, constant current driver (<20% THD, >0.9 PF). Standard 0-10V Dimming with 1-100% range.

FINISH: White glossy antimicrobial polyester powder coat finish following iron phosphate pre-treatment.


GASKET: Closed cell EPDM and closed cell silicone gaskets prevent air contaminants from entering the fixture.

INSTALLATION: Surface installation.


LABEL: Suitable for Wet Locations. IP53 Rating. Meets standards for ISO3/Class 1 Cleanrooms. NSF2 Splash/Non-Food zone. This product is Made in America and complies with the Buy American Act (BAA) and the Build America, Buy American Act (BABAA).



AFO2



AFO4



AFO8

PERFORMANCE DATA

*Data is with 80 CRI chip. LEDs are frequently updated, therefore values may change without notice.

MODEL	OUTPUT	LUMENS DELIVERED	EFFICACY (lm/w)	INPUT POWER (W)	WEIGHT
AFO2	ST = Standard	1820	140	13	3 lbs.
	HG = High	3250	130	25	
AFO4	ST = Standard	3500	140	25	5 lbs.
	HG = High	6500	130	50	
AFO8	ST = Standard	7000	140	50	8 lbs.
	HG = High	13000	130	100	

DIMENSIONAL DATA