

# 51HD SERIES: QUICK SHIP

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 PRODUCT: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_



51HD Quick Ship Series

## PRODUCT FEATURES

- Intended for Apartment Buildings, School Campuses, Public Housing Complexes, Transportation Terminals, Utility Corridors, Hotels, Locker Rooms, and more
- 10 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- Surface mount installation
- This product was Made in America and complies with the Buy American Act (BAA), and Build America, Buy America Act (BABAA)
- The 51HD is covered by the New Star Promise

## ORDERING INFORMATION

Example: 51HD4-L235-1C-B-90C-12-QS



51HD4					
Series	Lumen Output*	Color Temp.	Circuits	Lens	CRI
	L2 = Low L4 = High	35 = 3500K 40 = 4000K 50 = 5000K	1C = 1 Circuit 2C = 2 Circuits*	B = .125 Prismatic Poly. C = .156 Prismatic Poly. D = .187 Prismatic Poly.	80C = 80 CRI 90C = 90 CRI
	*Subject to change. Performance Data on Page 3.		*For L4 output only.		

				QS
<b>Voltage</b> 12 = 120V 27 = 277V UN = Universal (120V-277V)	<b>Driver</b> DM = 0-10V dimming with 10-100% range DMI = 0-10V dimming with 1-100% range	<b>Options</b> FZ1 = Fuse (120V) FZ2 = Fuse (277V) EL1 = Emergency Battery LED Low (1100-1250lm)* EL2 = Emergency Battery LED Low (1900-2000lm)* WL = Wet Location (Covered Ceiling Only) AH = Allen Head Screw with Center Pin AM = Antimicrobial Paint SD2 = Step Dim. Driver (50-100%) SD3 = Step Dim. Driver (30-70-100%) WP = 6ft. Flex Whip. Supply wires included only otherwise specified  *Consult factory for the CA Title 24 options. If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity.	<b>Quick Ship</b> QS = Quick Ship	



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
 (773) 847-1400  
[www.newstarlighting.com](http://www.newstarlighting.com)

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

# 51HD SERIES: QUICK SHIP



## SPECIFICATIONS

**Housing:** 16-Gauge cold rolled steel internally reinforced to provide double wall thickness at ends and corners.

**LENS:** .125" Clear prismatic UV-stabilized polycarbonate diffuser.

**LED:** Available in three color temperatures: 3500K, 4000K, and 5000K with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in a 25°C temperature ambient environment, compliant with IES LM-80 testing standards.

**ELECTRICAL:** 120-277VAC 50/60Hz, constant current driver (<20% THD, >0.9 PF). 0-10V dimming available with 10-100% range and 1-100% range. Must specify dimming under options.

**REFLECTOR:** Aluminum, removable and unitized with all electrical components for easy installation and maintenance.

**FASTENERS:** Tamper resistant Torx® head fasteners with center pin reject.


**FINISH:** White polyester powder coat finish following multistage iron phosphate pre-treatment.

**WARRANTY:** New Star Promise.

**INSTALLATION:** Surface installation. Hardware by others.

**LABEL:** Fixture is certified to UL standards. Suitable for Damp Locations.

## DIMENSIONAL DATA



The 51HD Quick Ship Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse\*.

\*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
(773) 847-1400  
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

# 51HD SERIES: QUICK SHIP



## PERFORMANCE DATA

\*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
51HD4	L2 = Low	4000K	5500	110	50
	L4 = High	4000K	11000	110	100



### New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609  
(773) 847-1400  
[www.newstarlighting.com](http://www.newstarlighting.com)

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.