

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 PRODUCT: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_

## PRODUCT FEATURES

- Intended for Commercial applications such as offices, medical office buildings, corridors, lobbies, waiting rooms, and more
- Aluminum mounting canopy included for top, end or back mount
- Red and/or green legend, optional single or double face
- Fixture is certified to UL standards for Damp Locations (0°C - 50°C). This product is Assembled in America and complies with Buy American Act requirements when specified



CCEL Series



## ORDERING INFORMATION

Example: CCEL-DF-RW-WH-WH

CCEL				
<b>Series</b>	<b>Face</b> SF = Single Face DF = Double Face	<b>Lettering</b> RW = Red Letters GW = Green Letters	<b>Panel</b> C = Clear* M = Mirror WH = White  *With single face only	<b>Housing Color</b> WH = White BK = Black AL = Aluminum

<p><b>Battery</b>                      Blank = AC-Only                      EM = Emergency Battery</p>	<p><b>Options</b>                      CUS = Custom Signage*                      SDT = Self-Diagnostics*                      2C/120 = Dual Circuit with 120V Input**                      2C/270 = Dual Circuit with 277V Input**                      SPV = 208/220/240V, 50/60Hz***                      BAA = Buy American Act compliant</p> <p>*Consult factory                      *Available only with EM units                      **Not available with EM units                      ***Not available with SDT</p>
--	--



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
 (773) 847-1400  
 www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

## SPECIFICATIONS

**CONSTRUCTION:** Extruded aluminum housing, also available in white or black powder coat finishes. Self-adhesive Chevron appliques and guide template provided for directional indication.

**LENS:** UV-stabilized clear acrylic edgelit panel provides consistent, uniform illumination. Double face utilizes factory installed silver or white mylar background panel.

**ELECTRICAL:** Dual 120/277 voltage standard, optional 208/220/240 Volt, 50/60Hz. Energy-efficient, long life Red or Green LEDs. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### ELECTRICAL OPTIONS:

**SDT:** Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

**2C-120/277V:** Dual circuit option on the AC-only unit enables it to be connected to two different power supplies at the same time.

**FASTENERS:** Stainless steel Philips fasteners.

**INSTALLATION:** Aluminum mounting canopy included for top or end mount.

**WARRANTY:** Five (5) year warranty on all electronics and housing. Battery prorated for five years.

**LABEL:** Fixture UL Listed for Damp Locations (0°C - 50°C). This product is UL924 Listed and meets or exceeds NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. Certified to CEC under Title 20 Regulations. This product is Assembled in America and complies with the Buy American Act (BAA) when specified.

## DIMENSIONAL DATA

