

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



CCREL Series

PRODUCT FEATURES

- Intended for Commercial applications such as offices, medical office buildings, corridors, lobbies, waiting rooms, and more
- Recessed ceiling or optional wall mount installation
- Red or green legend, optional single or double face
- Fixture is certified to UL standards for Damp Locations, UL924 Listed and meets or exceeds NFPA 101 Life Safety Code
- This product is Assembled in America and complies with Buy American Act (BAA) requirements when specified

ORDERING INFORMATION

Example: CCREL-SF-RW-C-WH



CCREL					
Series	Face SF = Single Face DF = Double Face	Lettering RW = Red Letters GW = Green Letters	Panel C = Clear* M = Mirror WH = White *With single face only	Housing Color WH = White BK = Black AL = Aluminum	Options CUS = Custom Signage EM = Emergency Battery* SDT = Self-Diagnostics** WM = Wall Mount*** SPV = 208/220/240 Volt, 50/60Hz**** 120 = Dual Circuit with 120V Input+ 270 = Dual Circuit with 277V Input+ USA = Assembled in USA BAA = Buy American Act compliant *If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity **Available only with EM units ***With single face only ****Not available with SDT +Not available with EM units



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
 www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

CONSTRUCTION: Extruded aluminum housing. Extruded aluminum trim assembly is easily detachable, providing accessibility for service or maintenance. Single or double face configurations. Self-adhesive Chevron appliques and guide template provided for directional indication. Double face utilizes factory installed silver or white mylar background panel.

LENS: UV-stabilized, ultra-clear acrylic edgelit panel provides consistent, uniform illumination.

LED: Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL: Dual 120V/277V standard. Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only).

INSTALLATION: Recessed ceiling or optional wall mount installation.

FINISH: Available in black or white power-coated finishes.

WARRANTY: Limited five (5) year warranty.

LABEL: Fixture is certified to UL standards for Damp Locations, UL924 Listed, and meets or exceeds NFPA 101 Life Safety Code. This product is Made in America and complies with the Buy American Act (BAA) when specified.

DIMENSIONAL DATA

