

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

PRODUCT: \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

PRODUCT FEATURES

- Intended for Commercial applications such as offices, medical office buildings, corridors, lobbies, waiting rooms, and more
- Ceiling or wall surface mount installation
- Red or green legend, optional single or double face
- Fixture is certified to UL standards for Damp Locations
- This product is Assembled in America and complies with Buy American Act (BAA) requirements



CCREL Quick Ship Series

ORDERING INFORMATION

Example: CCREL-SFRW-CWH



CCREL					
Series	Face	Lettering	Panel	Housing Color	Options
	SF = Single Face DF = Double Face	RW = Red Letters GW = Green Letters	C = Clear* M = Mirror WH = White  *With single face only	WH = White BK = Black AL = Aluminum	CUS = Custom Signage EM = Emergency Battery* SDT = Self-Diagnostics** WM = Wall Mount*** SPV = 208/220/240 Volt, 50/60Hz**** 120 = Dual Circuit with 120V Input+ 270 = Dual Circuit with 277V Input+ USA = Assembled in USA  *If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity **Available only with EM units ***With single face only ****Not available with SDT +Not available with EM units

## SPECIFICATIONS

**CONSTRUCTION:** Extruded aluminum housing. Extruded aluminum trim assembly is easily detachable, providing accessibility for service or maintenance. Single or double face configurations. Self-adhesive Chevron appliques and guide template provided for directional indication. Double face utilizes factory installed silver or white mylar background panel.

**LENS:** UV-stabilized, ultra-clear acrylic edgelit panel provides consistent, uniform illumination.

**LED:** Ultra bright, energy efficient, long life Red or Green LEDs.

**ELECTRICAL:** Dual 120V/277V standard. Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only).

**INSTALLATION:** Ceiling or wall surface mount installation

**FINISH:** Available in black or white power-coated finishes.

**WARRANTY:** Limited five (5) year warranty.

**LABEL:** Fixture is certified to UL standards for Damp Locations. This product is Made in America and complies with the Buy American Act (BAA).

## DIMENSIONAL DATA

