

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Vanity mirrors for Healthcare, Assisted Living, Medical Office Buildings, Multi-Family or other commercial bathroom settings
- Low profile, ADA-compliant surface mount in rectangle or oval shapes
- Corrosion-resistant, copper-free mirror provides clear imaging, high reflectance, better color rendition and durability
- LED Lighting with high color rendering (90 CRI), as well as red rendering (R9>60) for skin tone evaluation
- Amber (585nm-595nm) or White (2700K-4000K) nightlight options
- Fixture is certified to UL Standards by Intertek Testing Laboratory for non-IC. NSF2 Splash/Non-Food Zone listed



CCVMR



CCVMO

ORDERING INFORMATION

Example: CCVMR-35-AMB-90C-SB-UN-DM2



CCVM					90C
Series	Style R = Rectangle O = Oval	Color Temp. 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	Nightlight AMB = Amber (585nm-595nm) 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	Frame Finish* SB = Brushed Stainless Steel ALM = Almond (RAL 9001) ARG = Argento (RAL 7035) BLK = Black BL = Blue (RAL 5009) LB = Light Blue (RAL 6034) LIC = Lilac (RAL 4009) PG = Pistachio Green (RAL 6024) WH = White CC = Custom RAL Color** *Antimicrobial finishes are standard. **Color swatches on Page 3.	CRI 90C = 90 CRI

UN	DM2	
Voltage UN = Universal (120-277V)	Driver Type DM2 = 0-10v 0-100% dimming range or Triac/Phase Dimming.	Options TB = 5° Tilt Bracket* *Only available in CCVMR (Rectangle)

SPECIFICATIONS

CONSTRUCTION: Surface mount cold rolled steel housing.
Closed-cell neoprene gasket seals mirror to wall.

FRAME: Mirror frame is constructed of stainless steel.
Antimicrobial white, black or custom powder coat finishes are available. Frame secured to housing with flush stainless steel tamper-resistant Torx® fasteners.

MIRROR: Corrosion and scratch-resistant, copper-free mirror provides clear imaging, high reflectance, better color rendition and durability. LED shielding is constructed of scratch-resistant polycarbonate lens.

LED: LED modules are available in 2700K, 3000K, 3500K, and 4000K with maximum 3-step MacAdam variation allowance. Minimum 90CRI standard. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature, compliant with IES LM-80 testing standards.

DRIVER: Integral Constant Voltage 60W 12v/24VDC, 100-277v, 50/60Hz, 0-10v dimming with 0-100% range or, Triac/Phase dimming optional.

FASTENERS: Flush stainless steel Torx® head fasteners with center reject pin.



FINISH: Brushed stainless steel frame standard. Choice of white, black or custom color antimicrobial polyester powder coat finish following multistage iron phosphate pretreatment on all exposed surfaces, unless otherwise specified.

INSTALLATION: Surface mount installation.

WARRANTY: Five (5) year warranty period.

LABEL: Fixture is certified to UL Standards by Intertek Testing Laboratory for non-IC. Certified for NSF2 Splash Zone/Non-Food Zones.

DIMENSIONAL DATA



PERFORMANCE DATA

*LEDs are frequently updated therefore values may change without notice.

	CRI	COLOR TEMP	TOTAL DELIVERED LUMENS	INPUT POWER (W)	EFFICACY(lm/W)	WEIGHT (lbs)
CCVMR (RECTANGLE)	90	3000K	737.3	57.7	10.9	25
		3500K	776.2	60.7	11.5	
		4000K	817	63.9	12.1	
		5000K	860	67.3	12.7	
		Amber	82.6	65.6	1.2	
	CRI	COLOR TEMP	TOTAL DELIVERED LUMENS	INPUT POWER (W)	EFFICACY(lm/W)	WEIGHT (lbs)
CCVMO (OVAL)	90	3000K	588.2	12	41.8	25
		3500K	619.1	12.6	44.0	
		4000K	651.7	13.3	46.4	
		5000K	686	14	48.8	
		Amber	145	2	69.3	


FINISHES

Almond (RAL 9001)
(ALM)
138/15003

Argento (RAL 7035)
(ARG)
138/90470

Blue (RAL 5005)
(BL)
149/47310

White
(blank)



Light Blue (RAL 5024)
(LB)
138/50034

Lilac (RAL 4009)
(LIC)
149/34740

Pistachio Green (RAL 6024)
(PG)
230/51120

Black
(BLK)



New Star Lighting
2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.