

PROJECT: _____

TYPE: _____

PRODUCT: _____

APPROVED BY: _____



PRODUCT FEATURES

- Ligature resistant for Behavioral Health applications
- Nominal one foot height
- Field Selectable CCT (2700K-5000K)
- Optional amber (585-595nm) night light
- Fixture is IP64 rated per IEC60598



DCF Series

ORDERING INFORMATION

Example: DCFB-1-CCT-PM-BL-UN-DM1



DCF		1	CCT		
Series	Style B = Box O = Oval V = V-Shape	Size* 1 = 1ft *Nominal Size. Dimensional Data on Page 2.	Field-Selectable Color Temp. CCT = 2700-5000K	Lens PM = Opal PMMA (std.) XXX = PositiveCare Graphics image choices can be found HERE* *Insert image number from PositiveCare Gallery	Finish* BLANK = Standard White ALM = Almond ARG = Argento BLK = Black BL = Blue (RAL 5009) LB = Light Blue (RAL 6034) LIC = Lilac (RAL 4009) PG = Pistachio Green CC = Custom RAL Color** *Color swatches on Page 3.

Voltage 12 = 120V 27 = 277V UN = Universal (120V-277V)	Driver Type DM1 = 0-10V Dimming with 1-100%
---	--

SPECIFICATIONS

CONSTRUCTION: Tapered diecast aluminum housing frame, and heavy-weight heavy-gauge steel baseplate. Concealed Torx® fastener on top of housing for easy installation.

LENS: Opal PS diffusing lens, silicone sealed to housing. Optional PositiveCare graphic images can be incorporated onto lens, second surface printing for cleanability. For image gallery, click [here](#).

LED: Available in five field-selectable color temperatures 2700K, 3000K, 3500K, 4000K and 5000K with maximum 3-step MacAdam variation allowance. Tunable White option in 2700K-5000K. Tunable White drivers must be selected.

ELECTRICAL: 120-277Vac 50/60Hz, constant current driver (<30% THD, >0.9 PF). Standard 0-10V Dimming with 1-100% range.

FINISH: White antimicrobial power coat finish standard, additional color choices available. Consult factory for custom colors.

WARRANTY: New Star Promise.

LABEL: Certified to UL standards by Intertek Testing Laboratory. IP65 rated per IEC60598. IK10 Listed per IEC60068-2-75. This product complies with the Buy American Act (BAA)




The DuraCare™ Frame Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.





*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.

DIMENSIONAL DATA



MODEL	HEIGHT	DEPTH	WIDTH	WATTAGE	CCT	LUMEN
DCFB	13.86"	1.06"	11.89"	11	5	850
DCFV	13.86"	1.06"	13.39"	11	5	850
DCFO	15.35"	1.06"	10.92	11	5	850

FINISHES

Almond (ALM) 138/15003	Argento (ARG) 138/90470	Blue (B) 149/47310	White (Blank)
			
Light Blue (LB) 138/50034	Lilac (LIC) 149/34740	Pistachio Green (PG) 230/51120	Black (BLK)
