

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



PRODUCT FEATURES

- Ligature-resistant design intended for behavioral health applications
- Up to 1125 lumens per foot with custom tuning of outputs in provided in Symmetric and Asymmetric Wall wash distributions
- Available in 2'-8' lengths in 1' increments with optional end mount thru wiring for flush, end-to-end mounting
- Extruded Aluminum housing and one piece, beveled fit aluminum door features continuous lens retention, integrated close cell gasketing and secured via tamper resistant Torx head fasteners
- Certified to UL standards by Intertek Testing Laboratory. IP65 rated per IEC60598. NSF2/Non-Food Zone Listed, IK10 Listed per IEC60068-2-75. IC-Rated housing.
- This product is Made in America and complies with the Buy American Act (BAA), and the Build America, Buy America Act (BABAA)



DCL Series

ORDERING INFORMATION

Example: DCL48-FL-500-35-90C-AM-D-ASY-UN-DM1



DCL						
Series	Nominal Length*	Ceiling Configuration	Lumen Output	Color Temp.	CRI	Finish
	24 = 2'	TB9 = 9/16" Lay-In Grid	500 = 500LM/FT-Min	30 = 3000K	80C = 80 CRI	AM = Antimicrobial White
	36 = 3'	TB15 = 15/16" Lay-in Grid	750 = 750LM/FT	35 = 3500K	90C = 90 CRI	C = Custom Color*
	48 = 4'	TG9 = 9/16" Tegular Grid	1125 = 1125LM/FT-Max	40 = 4000K		*RAL number required.
	72 = 6'	TG15 = 15/16" Tegular Grid	CL = Custom Lumens*	RGBW/30 = RGB + 3000K*		
	96 = 8'	FL = Flange*		RGBW/40 = RGB + 4000K*		
		NFL = No Flange	*Outputs between Min. and Max. available. Must be specified at time of quote. Must not exceed fixture maximum output.	* Must use with DMX Driver		
		ST = Screw Slot		Tunable White*		
		TM = Trimless Mud-In for 5/8" Drywall*		TW1 = 2700K to 5000K		
	*Available in 1' increments. Consult factory for other lengths.	*Suitable for use with WM option, refer to page 2.		TW2 = 2700K to 6500K		
				*Must specify Tunable White Driver.		

D				
Outer Lens	Inner Lens (Diffuse Optical Film)	Voltage	Driver Type	Options
D = .250 Clear Poly.*	SYM = Symmetric ASY = Asymmetric Wall Wash	12 = 120V 27 = 270V 34 = 347V* UN = Universal (120V-277V)	DM1 = 0-10V Dimming with 1-100% range DMT = 0-10V & TRIAC/ELV* *Must specify with 120V.	FZ1 = Fuse (120V) FZ2 = Fuse (277V) CP = Chicago Plenum Rated B(#)= 10 watt Battery Pack with test switch* GTD(1) = Generator transfer device* WM = Wall Mount RMM = Row Mount Middle Feed Fixture** RME = Row Mount End Feed Left Fixture***
*Asymmetric distribution supplied with .187 clear polycarbonate lens.		*347V only available with DM1 Drivers.	RGBW Driver DMX = DMX Driver** **The DMX driver is compatible for RGBW options	*Available for fixture lengths of 4' or greater. **Flange is removed from both ends of fixture, refer to drawing on Page 2. ***If ASY is specified, one flange is removed. Adjust door mounting to direct asymmetric beam as required.
			Tunable White Driver* DALI8 = 2-Channel DALI Type 8 with 1-100% TW0 = 2-Channel 0-10V *Tunable White Driver requires choice of TW1 or TW2 in Color Temp column.	



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

SPECIFICATIONS

HOUSING: Extruded aluminum construction with sheet metal endcaps. Closed cell neoprene pad in doorframe.

LENS: Clear polycarbonate outer lens with inner optical diffusion lens, providing either asymmetric or symmetric distribution.

DOORFRAME: Die-formed aluminum doorframe, with antimicrobial white powder-coat finish, secured with tamper-resistant Torx® fasteners. Safety aircraft cable also secures doorframe to housing for easy maintenance.

LED: Available in three color temperatures 3000K, 3500K, and 4000K with maximum 3-step MacAdam variation allowance. Tunable White and RGBW Options available. Minimum 50,000 hours with 85% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

ELECTRICAL: Standard 120-277VAC 50/60Hz or 347VAC 60Hz electrical input with serviceable constant-current drivers (<10%THD, >0.90 PF). 0-10V Dimming with 1-100% range.

TUNABLE DRIVER OPTIONS:

DALI8 - DALI Type 8 (One DALI Address)

TW0 - Two channel 0-10V dimming: one channel for brightness, one channel for CCT

FINISH: White polyester powder coat finish following multi-stage iron phosphate pretreatment. Optional antimicrobial finish for all room side exposed surfaces available.

INSTALLATION: Recessed Grid, Screw Slot Grid, Drywall Flange, Drywall Flangeless and Mud-In Flange options.

WARRANTY: Five (5) year warranty.

LISTINGS: Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 Rating per IEC6598. Certified for NSF2 Splash Zone/ Non-Food Zones. IC Rated. Standard CCEA compliance. This product is Made in America and complies with the Buy American Act (BAA).



The DuraCare™ Linear Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.


*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.

DIMENSIONAL DATA


		Fixture Length				
		2'	3'	4'	6'	8'
		(24")	(36")	(48")	(72")	(96")
Mounting	ST	23.875	35.87	47.87	71.87	95.87
	TB9	23.87	35.87	47.87	71.87	95.87
	TB15	23.87	35.87	47.87	71.87	95.87
	TG9	23.87	35.87	47.87	71.87	95.87
	TG15	23.5	35.5	47.5	71.5	95.5
	NFL/TM	23.87	35.87	47.87	71.87	95.87

*Additional dimensional information on page 3


END FEED CONFIGURATION



WALL MOUNT INSTALLATION



DIMENSIONAL DATA (CONT.)



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

PERFORMANCE DATA*

*Data is based on testing at 4000K.

MODEL	DISTRIBUTION	LUMENS PER FOOT	EFFICACY (lm/w)	INPUT POWER (W)
DCL24	SYMMETRIC	500	90	11
		750	90	16
		1125	90	25
	ASYMMETRIC	500	88	11
		750	88	17
		1125	88	25
DCL36	SYMMETRIC	500	90	16
		750	90	24
		1125	90	37
	ASYMMETRIC	500	88	17
		750	88	26
		1125	88	38
DCL48	SYMMETRIC	500	90	22
		750	90	32
		1125	90	50
	ASYMMETRIC	500	88	22
		750	88	34
		1125	88	50
DCL72	SYMMETRIC	500	90	33
		750	90	49
		1125	90	75
	ASYMMETRIC	500	88	34
		750	88	50
		1125	88	75
DCL96	SYMMETRIC	500	90	44
		750	90	65
		1125	90	99
	ASYMMETRIC	500	88	45
		750	88	67
		1125	88	100


MULTIPLIERS

CRI	MULTIPLIER
80 CRI	1
90 CRI	0.95


CCT	MULTIPLIER
3000K	0.95
3500K	0.98

PHOTOMETRIC CURVES

SYMMETRIC:



ASYMMETRIC WALL WASH:



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.