# **DURACARE MODEX**<sup>™</sup> SERIES

PROJECT:
ТҮРЕ:
PRODUCT:
APPROVED BY:

### **PRODUCT FEATURES**

- Ligature-resistant features to support Behavioral Health applications
- 2" Depth accommodates shallow wall plenums and modular rooms
- Tamper-resistant Torx® fasteners with center pin reject
- · Single Face available with red or green lettering
- NSF2 Splash/Non-Food Zone listed. Fixture is certified to UL standards for Wet Locations. IP65 Rated per IEC60598. Meets standards for ISO 3/Class 1 Cleanrooms
- This product is Made in America and complies with the Buy American Act, and the Build America, Buy America Act

#### **ORDERING INFORMATION**

Example: DCMOD-HS-OS-RW





DCMOD				
Series	Housing	Overlap Frame	Lettering	Options
	HP = 20Ga. SS Painted	<b>OP</b> = 18Ga. SS Painted	RW = Red Letters	<b>EM</b> = Emergency Battery (remote)
	HS = 20Ga. SS Mill Finish	<b>OS</b> = 18Ga. SS Brushed	<b>GW</b> = Green Letters	

#### **SPECIFICATIONS**

HOUSING: 20-Gauge formed stainless steel housing with continuous seam welds.

FRAME: Single face overlapping doorframe in 18-gauge stainless steel.

LENS: .125 Clear polycarbonate lens.

**LED:** Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

**ELECTRICAL:** Long life 7W LED system illuminates red or green legend. Universal voltage (120V-277V).

**LEGEND:** Legend illuminated by white LEDs with red or green lens. Lettering six inches high with .750" stroke. Chevron arrows are field-selectable for the desired direction.

**FINISH:** White glossy antimicrobial powder coat finish following multi-stage iron phosphate pre-treatment. Brushed stainless steel overlapping frame will be left unpainted if specified.

FASTENERS: Tamper-resistant Torx® fasteners with center pin reject.

**GASKET:** Closed-cell EPDM and closed-cell silicone gaskets prevent air contaminants from entering the fixture.

INSTALLATION: Recessed installation. Suitable for modular walls.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rating per IEC60598. Meets standards for ISO3/Class 1 Cleanrooms. NSF2 Splash/Non-Food Zone. UL924 Rated. This product is Made in America and complies with the Buy American Act (BAA).

WEIGHT: 10 lbs.



New Star Lighting 2225 W Pershing Rd, Chicago, IL 60609 (773) 847-1400 www.newstarlighting.com Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

## ★ New StarLighting

## **DURACARE MODEX**<sup>™</sup> SERIES

### **DIMENSIONAL DATA**







New Star Lighting 2225 W Pershing Rd, Chicago, IL 60609 (773) 847-1400 www.newstarlighting.com Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.