

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



PRODUCT FEATURES

- Ligature-resistant features to support Behavioral Health applications
- 2" Depth accommodates shallow wall plenums and modular rooms
- Tamper-resistant Torx® fasteners with center pin reject
- Single Face – available with red or green lettering
- NSF2 Splash/Non-Food Zone listed. Fixture is certified to UL standards for Wet Locations. IP65 Rated per IEC60598. UL924 Listed, and meets or exceeds NFPA 101 Life Safety Code Meets standards for ISO 3/Class 1 Cleanrooms
- This product is Made in America and complies with the Buy American Act (BAA), and the Build America, Buy America Act (BABAA)
- The Duracare MODEX™ Series is covered by the New Star Promise



DCMOD Series



ORDERING INFORMATION

Example: DCMOD-HS-OS-RW-90C

DCMOD					
Series	Housing HP = 20Ga. SS Painted HS = 20Ga. SS Mill Finish	Overlap Frame OP = 18Ga. SS Painted OS = 18Ga. SS Brushed	Lettering RW = Red Letters GW = Green Letters	CRI 80C = 80 CRI 90C = 90 CRI	Options EM = Emergency Battery (remote) AM = Anti-microbial finish for all room side exposed surfaces

SPECIFICATIONS

HOUSING: 20-Gauge formed stainless steel housing with continuous seam welds.

FRAME: Single face overlapping doorframe in 18-gauge stainless steel.

LENS: .125 Clear polycarbonate lens.

LED: Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

ELECTRICAL: Long life 7W LED system illuminates red or green legend. Universal voltage (120V-277V).

LEGEND: Legend illuminated by white LEDs with red or green lens. Lettering six inches high with .750" stroke. Chevron arrows are field-selectable for the desired direction.

 The DuraCare MODEX™ Series is covered by our New Star Promise. Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.

*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.

FINISH: White polyester powder coat finish following multi-stage iron phosphate pretreatment. Optional antimicrobial finish for all room side exposed surfaces available.

FASTENERS: Tamper-resistant Torx® fasteners with center pin reject.

GASKET: Closed-cell EPDM and closed-cell silicone gaskets prevent air contaminants from entering the fixture.

INSTALLATION: Recessed installation. Suitable for modular walls.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rating per IEC60598 UL924 Listed, and meets or exceeds NFPA 101 Life Safety Code. Meets standards for ISO3/Class 1 Cleanrooms. NSF2 Splash/Non-Food Zone. UL924 Rated. This product is Made in America and complies with the Buy American Act (BAA).

WEIGHT: 10 lbs.

DIMENSIONAL DATA

