

STARMED™ DOWNLIGHT SERIES: QUICK SHIP

PROJECT: _____


TYPE: _____

PRODUCT: _____

APPROVED BY: _____

PRODUCT FEATURES

- Intended for Patient Rooms, Nurses’ Stations, Exam Rooms, Lobbies, Common Areas, and more
- 10 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- Enclosed aluminum or cold rolled steel housing with extruded aluminum heat sink
- Available in 6” aperture and 8” aperture
- Sealed for infection control and cleanability. Suitable for Wet Location installations, thru-branch wiring, IP65 rating, meets ISO 4/Class 10 Cleanrooms, and NSF2 Splash/Non-Food Zone
- This product is Made in America and complies with the Buy American Act (BAA) requirements



DLM SERIES

ORDERING INFORMATION

Example: DLM6-HA-L135-90C-A/A-A-3-UN-QS



DLM	6	HA				/	
Series	Aperture 6 = 6 inch	Housing HA = 16 Ga. Aluminum Painted	Lumen Output* L4 = 25W L5 = 37W L6 = 45W L7 = 52W *Subject to change. Performance Data on page 3.	Color Temp. 35 = 3500K 40 = 4000K	CRI 80C = 80 CRI 90C = 90 CRI	Outer Lens A = .125 Clear Acrylic B = .125 Clear Poly. C = .187 Clear Poly. D = .250 Clear Poly. O = None	Inner Lens A = .125 Prismatic Acrylic B = .125 Prismatic Poly. C = .156 Prismatic Poly. D = .125 White Frosted Poly.

	3			
Trim A = .080 Aluminum Painted B = 18Ga. CRS Painted *Additional fees may apply. Consult factory for details.	Reflector 3 = Low Gloss White	Voltage 12 = 120V 27 = 277V UN = Universal (120V-277V)	Options TH = Tamper-resistant Torx® head fasteners* *TH are not NSF-rated.	QS = Quick Ship

STARMED™ DOWNLIGHT SERIES: QUICK SHIP NewStarLighting

SPECIFICATIONS

CONSTRUCTION: 16-Gauge aluminum cold rolled steel sealed housing with an extruded aluminum heat sink designed for maximum thermal dissipation.

LENS: Features a prismatic inner lens and clear outer lens in choice of acrylic, polycarbonate, or glass options.

LED: Available in two color temperatures 3500K and 4000K with maximum 3-step MacAdam variation allowance. Other color temperatures available in standard offering, consult factory. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

ELECTRICAL: 120-277VAC 50/60HZ electrical input high power factor electronic, constant current driver (<20% THD, >0.90 PF). Standard 0-10V Dimming with 1-100% range. Rated for through-branch wiring.

FASTENERS: Stainless steel Philips flat head fasteners with captive cage nuts. Finished to match trim.

FINISH: White antimicrobial polyester powder coat finish following multi-stage iron phosphate pretreatment on all exposed room-side painting surfaces, unless otherwise specified.

GASKET: Closed cell EPDM and closed cell silicone gaskets prevent air contaminations from entering the fixture.


INSTALLATION: Recessed installation.

WARRANTY: Limited Five (5) year warranty.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory for Non-IC and Wet Location installations (under covered ceiling). Suitable for through branch wiring. Certified IP65 per IEC 60598 and NSF2 Splash Zone/Non-Food Zone listed (with PH fasteners). Meets ISO4 (FED-STD-209E/Class 10) Cleanrooms. Optional MIL-STD-461G. This product is Made in America and complies with the Buy American Act (BAA) requirements.

DIMENSIONAL DATA

6" DOWNLIGHT



STARMED™ DOWNLIGHT SERIES: QUICK SHIP NewStarLighting

PERFORMANCE DATA

*LEDs are frequently updated therefore values may change without notice.

Model	Output	lum	lm/w	Wattage
DLM6 (90 CRI)	L4	1625	65	25
	L5	2220	60	37
	L6	2610	58	45
	L7	2860	55	52



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.