


HNL STEP LIGHT SERIES: QUICK SHIP



PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Intended for Fall Prevention in healthcare settings, including Patient Rooms, Patient Bathrooms, Corridors, Lobbies, Waiting Rooms, Nurses' Stations, and more
- 5 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- Four faceplate options: horizontal or vertical hood, horizontal louver, and open frame
- Constructed of durable die-cast aluminum with integral embedded driver (3W)
- Available in White CCTs: 3000K, 4000K, 5000K and Amber LED



HNL Quick Ship Series

ORDERING INFORMATION

Example: HNL-HH-30-80C-UN-NF-AM-QS



HNL			80C	UN		QS
Series	Faceplate HH = Horizontal Hood HL = Horizontal Louver OF = Open Frame* VH = Vertical Hood *Can be installed horizontally or vertically.	Color Temp. 30 = 3000K 40 = 4000K 50 = 5000K LA = Amber LED	CRI 80C = 80 CRI	Voltage UN = Universal (120V-277V)	Options NF = None AM = Antimicrobial White	QS = Quick Ship



New Star Lighting
 2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

HOUSING: Durable die-cast aluminum material. Available with four different faceplates: Horizontal Hood, Horizontal Louver, Open Frame (can be installed vertically or horizontally), and Vertical Hood.

LED: Available in three color temperatures 3000K, 4000K, and 5000K with maximum 3-step MacAdam variation allowance. Amber LED is also available. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

ELECTRICAL: Integrated embedded driver (3W). Standard 0-10V Dimming with 10-100% range.

FINISH: White polyester powder coat finish following multi-stage iron phosphate pretreatment. Optional antimicrobial finish for all room side exposed surfaces available. Custom color available, must specify RAL number and indicate if antimicrobial finish is needed (set-up fees may apply).


INSTALLATION: Recessed wall mount installation. J-Box and hardware by others.

WARRANTY: 5 Year Warranty.


LABEL: Fixture is certified to UL standards for Wet Location rating (under covered ceiling).

DIMENSIONAL DATA


HORIZONTAL HOOD WITH PH/OC




HORIZONTAL HOOD WITHOUT PH/OC




VERTICAL HOOD



OPEN FRAME (VERTICAL OR HORIZONTAL)



HORIZONTAL LOUVER



HNL STEP LIGHT SERIES: QUICK SHIP



PERFORMANCE DATA*

*LEDs are frequently updated therefore values may change without notice.

MODEL	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
HNL-OF	3000K	250	66	3.8
	4000K	240	63	3.8
	5000K	253	67	3.8
	Amber LED	170	45	3.8
HNL-VH	3000K	92	24	3.8
	4000K	82	22	3.8
	5000K	95	25	3.8
	Amber LED	61	16	3.8
HNL-HH	3000K	130	34	3.8
	4000K	120	32	3.8
	5000K	133	35	3.8
	Amber LED	88	23	3.8



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.