

PROJECT: _____
TYPE: _____
PRODUCT: _____
APPROVED BY: _____



MODex Series

PRODUCT FEATURES

- Intended for Modular Cleanrooms, Hospitals, Hi-Tech Manufacturing, Laboratories, Food Processing Facilities, Commercial Kitchens, and more
- 2" Depth accommodates shallow wall plenums and modular rooms
- Single Face - available with red or green lettering
- NSF2 Splash/Non-Food Zone listed. Fixture is certified to UL standards for Wet Locations, UL924 Listed, and meets or exceeds NFPA 101 Life Safety Code. IP65 Rated per IEC60598. Meets standards for ISO 3/Class 1 Cleanrooms
- This product is Made in America and complies with the Buy American Act (BAA), and the Build America, Buy America Act (BABAA)



ORDERING INFORMATION

Example: MOD-HS-OS-RW-90C

MOD					
Series	Housing HP = 20Ga. SS Painted HS = 20Ga. SS Mill Finish	Overlap Frame OP = 18Ga. SS Painted OS = 18Ga. SS Brushed	Lettering RW = Red Letters GW = Green Letters	CRI 80C = 80 CRI 90C = 90 CRI	Options EM = Emergency Battery (remote) *If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity.

SPECIFICATIONS

HOUSING: 20-Gauge formed stainless steel housing with continuous seam welds.

FRAME: Single face overlapping doorframe in 18-gauge stainless steel.

LENS: .125 Clear polycarbonate lens.

LED: Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

ELECTRICAL: Long life LED system illuminates Red or Green single face legend. 7W.

LEGEND: Legend illuminated by internal high output LEDs. Lettering 6" high with .750" stroke. Polycarbonate-red or green filter panel. Field selectable chevron.

WEIGHT: 10 lbs.

FINISH: White glossy antimicrobial polyester powder coat finish following multi-stage iron phosphate pre-treatment. Brushed stainless steel overlapping frame will be left unpainted if specified.

FASTENERS: Stainless steel Phillips fasteners. Finish to match frame.

GASKET: Closed-cell EPDM and closed-cell silicone gaskets prevent air contaminants from entering the fixture.

INSTALLATION: Recessed installation. Suitable for modular walls.

WARRANTY: Limited five (5) year warranty.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rating per IEC60598. Meets standards for ISO3/Class 1 Cleanrooms. NSF2 Splash/Non-Food Zone. UL924 Listed and meets or exceeds NFPA 101 Life Safety Code. This product is Made in America and complies with the Buy American Act (BAA) and the Build America, Buy America Act (BABAA).

DIMENSIONAL DATA

