

PROJECT: _____

TYPE: _____

PRODUCT: _____

APPROVED BY: _____



MUS

PRODUCT FEATURES

- Intended for Task Lighting, Patient Rooms, Nurse Stations, Medical Offices, Research Facilities, Laboratories, and more
- Available in three sizes: 2ft, 3ft, 4ft
- Easy installation with keyhole slots
- White antimicrobial finish standard
- Fixture is certified to UL standard by Intertek Testing Laboratory for Damp Locations
- This product is Made in America and complies with the Buy American Act requirements

ORDERING INFORMATION

Example: MUS2-HC-L135-A-UN



MUS				
Series	Size* 2 = 2ft 4 = 3ft *Nominal Size. Dimensional Data on Page 2.	Housing HC = 20Ga. CRS Painted HA = 16Ga. Alum. Painted *Remote Power Supply, ordered separately. Requires proper filter components supplied by others. Consult factory for additional information.	Lumen Output* L1 = Standard *Subject to change. Performance data on Page 3.	Color Temp. 30 = 3000K 35 = 3500K 40 = 4000K
A				
Lens A = .125 Prismatic Acrylic	Voltage 12 = 120V 27 = 277V 34 = 347V UN = Universal (120V-277V)	Options FZ1 = Fuse (120V) FZ2 = Fuse (277V) RM = Row Mount (consult factory) RS = Rocker Switch (120V) CO = Convenience Outlet (120V) OC = Occupancy Sensor		

SPECIFICATIONS

HOUSING: 20-Gauge formed cold rolled steel housing with continuous seam welds and ground smooth. Aluminum option available.

LENS: .125" prismatic acrylic lens.

LED: Available in three color temperatures 3000K, 3500K and 4000K with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature, compliant with IES LM-80 testing standards.

ELECTRICAL: 120/277VAC or 347VAC 50/60HZ standard integral 0-10V dimming driver available with 10-100% range.


FINISH: White antimicrobial powder coat finish following multi-stage iron phosphate pretreatment.

INSTALLATION: Surface installation. Keyhole slots for easy installation. Mounting screws are not provided.

WARRANTY: 5 Year Warranty.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory for Damp Location. This product was Made in America and complies with the Buy American Act requirements.

DIMENSIONAL DATA



PERFORMANCE DATA*

*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/w)	INPUT POWER (w)
MUS2	L1 = Standard	4000K	1250	100	12
MUS3	L1 = Standard	4000K	1875	100	18
MUS4	L1 = Standard	4000K	2500	100	25