

NOVA NEXC COMBO SERIES

HAZARDOUS LOCATION



PROJECT: _____

TYPE: _____

PRODUCT: _____

APPROVED BY: _____

PRODUCT FEATURES

- Certified for use in Hazardous Locations Class I, Division 2, Groups A, B, C and D
- Two fully adjustable, ultra bright 3.6 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing. Red or Green LED EXIT sign illumination.
- Fixture is certified to UL standards for Wet Locations (0°C– 50°C). IP66 rated per IEC60598. This product is Assembled in America and complies with Buy American Act (BABA)
- The NEXC Series is covered by the New Star Promise

ORDERING INFORMATION

Example: NEXC-SF-RW-G-12-15-CW



NEXC Series



NEXC						
Series	Face SF = Single Face* DF = Double Face** *Available only in 15W models **Available only in 12W models	Lettering RW = Red Letters GW = Green Letters	Housing Color G = Gray	Voltage 6 = 6 Volts 12 = 12 Volts	Wattage 12 = 12 Watts 15 = 15 Watts	Options SDT = Self-Diagnostics CW = Cold Weather TH = Torx® Head Fasteners* NH = No Heads *New Star Promise applies with TH option

NOVA NEXC COMBO SERIES

HAZARDOUS LOCATION



SPECIFICATIONS

CONSTRUCTION: Housing is fiberglass reinforced polycarbonate construction in gray finish. Corrosion-resistant enclosure with one piece, high-impact resistant UV stabilized polycarbonate lens and molded gasket with stainless steel fasteners. Snap-out Chevron directional indicators.

LENS: UV-stabilized clear Polycarbonate lens. Optional single face or double face with snap-out Chevron directional indicators.

ELECTRICAL: Dual 120/277 voltage standard. Energy-efficient, long life Red or Green LEDs. Unique bi-color LED indicator light alerts occupant on battery condition (Green = normal, Red = check battery). Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing.

6V/12V rechargeable NiCd battery (12W, 15W models). 6V/12V rechargeable sealed lead acid battery (28W model). Offers 4.8W, 7.8W, 20.8W of remote capacity (6V/12V DC output) standard on the 12W and 15W models.

Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

ELECTRICAL OPTIONS:

SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

CW: Optional internal heater and battery blanket for extreme cold temperature applications (-20°C - 50°C).

NH: No lamp heads attached to the unit, enabling it to be used as a remote capable EXIT sign.

FASTENERS: Stainless steel fasteners. Optional tamper-resistant Torx® head fasteners provides New Star Promise warranty.

INSTALLATION: Diecast mounting brackets provided for surface wall mount installation. Pre-installed conduit hub for conduit and pendant mount installation.

WARRANTY: Five (5) year warranty on all electronics and housing. Battery prorated for five years. New Star Promise warranty on physical construction when TH option is selected.

LABEL: Fixture UL Listed for Wet Locations (0°C - 50°C), and IP66 rated per IEC60598. Rated for Class I, Division 2, Groups A, B, C & D. This product meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. Certified to CEC under Title 20 Regulations. This product is Assembled in America and complies with the Buy American Act (BAA).




The NEXC Series is covered by our New Star Promise when Torx® head fasteners are selected.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.

*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.

DIMENSIONAL DATA



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.