

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



NSELN Series

PRODUCT FEATURES

- NYC-Compliant edgelit sign for stairwells, corridors, commercial settings, and more
- Ceiling or wall surface mount installation
- 8" EXIT red letters, optional single or double face
- Fixture is certified to UL standards for Damp Locations (0°C - 50°C), UL924 Listed and meets or exceeds NFPA 101 Life Safety Code



ORDERING INFORMATION

Example: NSELN-SF-RW-C-WH-SDT

NSELN		RW				
Series	Face SF = Single Face DF = Double Face	Lettering RW = Red Letters	Panel C = Clear* M = Mirror WH = White *With single face only	Housing Color WH = White BK = Black AL = Aluminum	Battery blank = AC Only EM = Battery Backup	Options SDT = Self-Diagnostics* SPV = 208/220/240 Volt, 50/60Hz** *Available only with EM units **Not available with SDT



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2026, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

CONSTRUCTION: Premium-grade, extruded aluminum housing (also available in optional black or white powder-coated finish). Single or double face configurations. Self-adhesive Chevron appliques and guide template provided for directional indication.

LENS: UV-stabilized clear acrylic edgelit panel provides consistent, uniform illumination. Double face utilizes factory-installed silver or white mylar background panel. New York City compliant 8" EXIT letters.

ELECTRICAL: Dual 120/277 voltage standard, 208/220/240 Volt 50/60Hz optional. Energy-efficient, long life Red LEDs. Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

FASTENERS: Stainless steel Philips fasteners.

INSTALLATION: Aluminum mounting canopy included for top, end or back mount. Available in optional black or white powder-coated finishes.

WARRANTY: Five (5) year warranty on all electronics and housing. Battery prorated for five years.

LABEL: Fixture UL Listed for Damp Locations (0°C - 50°C). This product is UL924 Listed and meets or exceeds NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

DIMENSIONAL DATA

