

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



NSELNR Series

PRODUCT FEATURES

- NYC-Compliant recessed edgELIT sign for stairwells, corridors, commercial settings, and more
- Recessed ceiling or optional wall mount installation
- 8" EXIT red letters, optional single or double face
- Fixture is certified to UL standards for Damp Locations (0°C - 50°C), UL924 Listed and meets or exceeds NFPA 101 Life Safety Code

ORDERING INFORMATION

Example: NSELNR-SF-RW-C-W-EM



NSELNR		RW				
Series	Face SF = Single Face DF = Double Face	Lettering RW = Red Letters	Panel C = Clear* M = Mirror WH = White *Single face only	Trim Plate WH = White BK = Black AL = Aluminum	Battery blank = AC Only EM = Battery Backup	Options SDT = Self-Diagnostics* SPV = 208/220/240 Volt, 50/60Hz** WM = Wall Mount*** *Available only with EM units **Not available with SDT ***Single face only

SPECIFICATIONS

CONSTRUCTION: Extruded aluminum housing. Extruded aluminum trim assembly is easily detachable from below, providing accessibility for service or maintenance. Available in black or white powder-coated finishes. Self-adhesive Chevron appliques and guide template provided for directional indication.

LENS: UV-stabilized clear acrylic edgelit panel provides consistent, uniform illumination. Double face utilizes factory installed silver or white mylar background panel. New York City compliant 8" EXIT letters.

ELECTRICAL: Dual 120/277 voltage standard, optional 208/220/240 Volt, 50/60Hz. Energy-efficient, long life Red or Green LEDs. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

ELECTRICAL OPTIONS:

SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

FASTENERS: Stainless steel fasteners.

INSTALLATION: Compatible with drywall or drop ceiling mount installations. Bar hangers included. Wall mount capability optional.

WARRANTY: Five (5) year warranty on all electronics and housing. Battery prorated for five years.

LABEL: Fixture UL Listed for Damp Locations (0°C - 50°C). This product is UL924 Listed and meets or exceeds NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

DIMENSIONAL DATA

