# **NSEM EMERGENCY** SERIES



PROJECT:
TYPE:
PRODUCT:
APPROVED BY:

#### **PRODUCT FEATURES**

- Intended for Public Areas, Schools, Locker Rooms, Corridors, Commercial Settings, and more
- 1.5 Watt (3 LEDs x 0.50 watt) per head
- · Unique all-inclusive lamp, reflector and lens assembly
- · Ceiling or wall surface mount installation
- Fixture is certified to UL standards for Damp Locations (0°C - 50°C), UL924 Listed and meets or exceeds NFPA 101 Life Safety Code
- This product is Assembled in America and complies with the Buy American Act (BAA)



**NSEM Series** 









## **ORDERING INFORMATION**

Example: NSEM-WH-RC

NSEM		
Series	Housing Color WH = White BK = Black	Options SDT = Self-diagnostics RC = Remote Capacity

# **NSEM EMERGENCY** SERIES



### **SPECIFICATIONS**

**CONSTRUCTION:** 5VA flame retardant, high-impact resistant, thermoplastic in white, black or gray finish.

ELECTRICAL: Dual 120/277 voltage standard. Unique bi-color LED indicator light alerts occupant on battery condition (Green = normal, Red = check battery). Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 3.6V long life, rechargeable NiCd battery. Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### **ELECTRICAL OPTIONS:**

**SDT:** Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

RC: Remote capacity of 2.5 watts.

FASTENERS: Stainless steel Philips fasteners.

**INSTALLATION:** Universal knockout pattern on back plate for surface mount. Suitable for wall or ceiling mount. Knockout for conduit applications.

FINISH: Available in white and black finish.

**WARRANTY:** Five (5) year warranty on all electronics and housing. Battery prorated for five years.

LABEL: Fixture UL Listed for Damp Locations (0°C - 50°C). This product is UL924 Listed and meets or exceeds NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. Certified to CEC under Title 20 Regulations. This product is Assembled in America and complies with the Buy American Act (BAA).

### **DIMENSIONAL DATA**



