

PROJECT: _____

TYPE: _____

PRODUCT: _____

APPROVED BY: _____

PRODUCT FEATURES

- Intended for vandal-prone applications including Public Areas, Corridors, Stairways, Parking Garages, Restrooms, Lobbies, Schools, and more.
- Available in three field-selectable lumen outputs (Low, Medium, High) and color temperatures (3000K, 4000K, and 5000K)
- 1-10V dimming standard
- Tamper resistant Torx® head screws
- Fixture is certified to UL standards. IP65 rating.



OSTS10 Series



OSTF10 Series

ORDERING INFORMATION

Example: OSTS10-LMS-CCT-UN-BK



OST			LMS	CCT		
Series	Style S = Semi Cover F = Full Cover	Size* 10" = 10" Wide 15" = 15" Wide	Selectable Lumen Output LMS = Low, Medium, High Lumen Output *Nominal size. Dimensional Data on Page 2.	Selectable Color Temp. CCT = 3000K, 4000K, 5000K	Voltage 34 = 347V UN = 120-277V	Finish BZ = Bronze BK = Black WH = White

SPECIFICATIONS

CONSTRUCTION: Die-cast aluminum housing. Available in a full or semi cover housing.

LED: Available in three field-selectable lumen outputs (Low, Medium, High) and color temperatures (3000K, 4000K, and 5000K).

ELECTRICAL: 1-10V dimming standard.

FINISH: Durable textured architectural bronze powder coat finish standard. Optional white or black finish available.

FASTENERS: Tamper resistant Torx® head screws.

INSTALLATION: Surface mount (hardware by others)

LABEL: Fixture is certified to UL standards. IP65 rating.



The Victory Narrow Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaries when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.



New Star Lighting
2225 W Pershing Rd, Chicago, IL 60609
(773) 847-1400
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

HOUSING: Die cast, one-piece marine grade aluminum.

LENS: UV stabilized white opal polycarbonate.

LED: Available in three color temperatures 3500K, 4000K and 5000K. 14.4W on 3 LED modules with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 80 CRI standard. Minimum 60,000h with 85% of lumen maintenance in 25°C ambient temperature environment, per IES TM-21 testing report.

REFLECTOR: 0.040" thick white aluminum for high reflectivity serves as heat sink and unitized with electrical components.

FASTENERS: Socket head cap screw.

FINISH: Durable polyester powder coat finish in black or white.

GASKET: An injection molded, continuous piece silicone rubber gasket to prevent infiltration.

MOUNTING: Surface wall mount installation.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratories.



The Ludo Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaries when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.

*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.

DIMENSIONAL DATA

