

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

PRODUCT: \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

PRODUCT FEATURES

The PositiveCare SKYLite Series provides a calming skylight appearance with the look of a luminous ceiling. Images are backlit by the luminaire recessed above within a standard grid. New Star offers a variety of high quality image overlays with the option of custom images (consult factory). Images can be configured as a standalone image or into a mural

- Intended for Exam Rooms, Medical Office Buildings, Lobbies, Pediatric Offices, Chapels and more
- Available in 1x1, 1x4, 2x2, 2x4, and 4x4 dimensions
- Designed to install into a grid ceiling with aluminum angled edge recessed frame that provides skylight appearance
- This product was Made in America and complies with the Buy American Act (BAA)



PCSKL Series

ORDERING INFORMATION

Example: PCSKL22-GAD-+PCC(11011)-30-1C-80C-UN-DMI



PCSKL				
Series	Size* 11 = 1x1 14 = 1x4 22 = 2x2 24 = 2x4 44 = 4x4  *Nominal size. Dimensional data on Page 2.	Mounting GAD = Grid with Aluminum Angled Recessed Frame	Ceiling Configuration X Y Z  X = Number of SKYLites per Mural Y = Horizontal length of Mural (Feet) Z = Vertical length of Mural (Feet)  * Configuration Example on Page 3. Custom configurations and shapes available, consult factory. Images may need to be edited based on layout.	Image blank = .125" Frosted Polycarbonate  Please <a href="#">CLICK HERE</a> to go to image selection guide(insert code in place)  +PCC(#) = custom image*  *Provide your own image (must be 150dpi at 100% image size).

	1C	80C			
Color Temp. 30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K TW1 = Tunable White 2700K to 5000K* TW2 = Tunable White 2700K to 6500K*  *Specify TW Driver under Options	Circuits 1C = 1 Circuit	CRI 80C = 80 CRI	Voltage 12 = 120V 27 = 270V 34 = 347V UN = Universal (120V-277V)	Driver Type DMI = 0-10V dimming with 1-100% range Driver  Tunable White Driver: DALI8 = 1-Channel Dali8* TW0 = 2-Channel 0-10V*  *Tunable White Driver requires choice of TW1 or TW2 in Lamp Color column. See Page 2 to specify system.	Other (Optional) FW = Flex whip (6' std)* CP = Chicago Plenum +E(#) = Emergency Section** +GTD(#) = Generator Transfer Device* EL1 = Emergency Battery  *Other lengths available; please consult factory.  **Specify quantity.

## SPECIFICATIONS

**CONSTRUCTION:** Die-formed 16Ga. aluminum painted with a polyester powder coat finish. Angled recessed frame illuminates the image by raising the SKYLite 3" above standard grid ceiling (15/16"). Frame painted in a white polyester powder coat finish unless otherwise specified.

**IMAGES:** Variety of high-resolution images designed to scale into large murals without pixelation. Images are printed on UV-stabilized polycarbonate lens material, unless otherwise specified.

**LENS:** 187" UV-stabilized polycarbonate lens with PositiveCare™ graphic image overlay (consult gallery on website for image options).

**LED:** Available in four white color temperatures 3000K, 3500K, 4000K, and 5000K (recommended). Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

**ELECTRICAL:** Standard 120-277VAC, 50/60Hz electrical input with constant current drivers (<210% THD, >0.90 PF).

**PCSKL22:** Input Power 40W

**PCSKL24:** Input Power 80W

**PCSKL44:** Input Power 120W

### OPTIONAL TUNABLE WHITE DRIVERS:

**DALI8** - DALI Type 8 (One DALI Address)

**TWO** - Two channel 0-10V dimming: one channel for brightness, one channel for CCT

**INSTALLATION:** Grid installation. Mounting for custom ceilings available, consult factory.


**WARRANTY:** 5 Year Warranty.

**LABEL:** Fixture is certified to UL standards by Intertek Testing Laboratory for Damp Locations. This product was Made in America and complies with the Buy American Act requirements.


## DIMENSIONAL DATA

Dimensions based on standard (15/16") Grid.  
Must have 4.5" ceiling clearance.

Image sits directly in frame



Must be secured  
extra security



	Frame Size	SKYLite Size (without Driver Box)	Total Height
<b>PCSKL11</b>	11.79" x 11.79" x 3.00"	11.81" x 11.81" x 0.56"	4.11"
<b>PCSKL14</b>	11.79" x 47.75" x 3.00"	11.81" x 47.75" x 0.56"	4.11"
<b>PCSKL22</b>	23.79" x 23.79" x 3.00"	23.62" x 47.75" x 0.56"	4.11"
<b>PCSKL24</b>	23.83" x 47.85" x 3.00"	23.62" x 47.62" x 0.56"	4.11"
<b>PCSKL44</b>	47.85" x 47.85" x 3.00"	47.64" x 47.64" x 0.56"	4.11"



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
(773) 847-1400  
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

CONFIGURATION EXAMPLE

Order quantity based on number of murals, not SKYLite fixtures.

Example: Qty 1: PCSKL24-M484-RT-UN-57 = 1 Mural consisting of 4 (2x4) SKYLite fixtures. Two SKYLite fixtures across (8') and two SKYLite fixtures down (4').

CONFIGURATION EXAMPLE #1
4 8 4

X Y Z

X = Number of SKYLite fixtures per Mural = 4 (2x4 SKYLite fixtures)

Y = Horizontal length of Mural (Feet) = 8ft

Z = Vertical length of Mural (Feet) = 4ft

CONFIGURATION EXAMPLE #2
4 4 8

X Y Z

X = Number of SKYLite fixtures per Mural = 4 (2x4 SKYLite fixtures)

Y = Horizontal length of Mural (Feet) = 4ft

Z = Vertical length of Mural (Feet) = 8ft

