

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 PRODUCT: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_



## PRODUCT FEATURES

- Ligature-resistant for behavioral health applications
- Architectural Cleanroom "V" troffer available in a 2x2 & 2x4
- Recessed ceiling mount; grid or flange. Compatible with 1.5" or 15/16" Grid Ceilings
- Fixture is certified to UL standards by Intertek Testing Laboratory. Suitable for Wet Locations. IP65 Rated per IEC60598, Meets ISO Class 3 (Fed Std. 209E/Class 10). IC-Rated per UL 1598
- This product is Made in America and complies with the Buy American Act (BAA), and the Build America, Buy America Act (BABAA)
- The DuraCare™ V Series is covered by the New Star Promise



DCV Series



## ORDERING INFORMATION

Example: SCVR22-DC-HC-L235-IC-A-90C-UN

SCV R			DC			
Series	Mounting R = Recessed (Grid/Flange)	Size* 22 = 2x2 24 = 2x4  *Nominal Size. Dimensional Data on Page 2.	DC = DuraCare™	Housing HC = 20Ga. CRS Painted HS = 20Ga. SS Brushed HP = 20Ga. SS Painted HA = .050Ga. Alum. Painted	Lumen Output* L2 = Low L4 = Medium L6 = High  *Subject to change. Performance Data on Page 3.	Color Temp. 35 = 3500K 40 = 4000K 50 = 5000K

IC		90C		VR-
<b>Circuits</b> IC = 1 Circuit .	<b>Lens</b> A = .125 Clear Acrylic B = .125 Clear Poly. C = .156 Clear Poly. D = .187 Clear Poly. E = .250 Clear Poly.  *Inner lens is a .125 White Frosted Acrylic for maximum diffusion.	<b>CRI</b> 90C = 90 CRI	<b>Voltage</b> 12 = 120V 27 = 277V UN = Universal (120V-277V)	<b>Options</b> FZ1 = Fuse (120V) FZ2 = Fuse (277V) EL1 = Emerg. Bat. LED Low (10W)* EL2 = Emerg. Bat. LED High (20W)* LN = LED Night Light** IP66 = IP66 Rated  *If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity. **3500K non-dimming Night Light with integrated switch allows light levels at 100%, 70%,40% and 10%.



**New Star Lighting**  
 2225 W Pershing Rd, Chicago, IL 60609  
 (773) 847-1400  
[www.newstarlighting.com](http://www.newstarlighting.com)

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

## SPECIFICATIONS

**HOUSING:** 20-Gauge formed cold rolled steel housing with continuous seam welds. Aluminum and stainless steel options available. Overlapping frame to match housing material. Philips flat heat fasteners secure doorframe to housing.

**LENS:** .125" White frosted acrylic inner lens. Options for outer lens includes clear acrylic or polycarbonate.

**LED:** Available in three color temperatures 3500K, 4000K, and 5000K with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in an ambient environment 25°C temperature, compliant with IES LM-80 testing standards. Minimum 80 CRI standard with optional minimum 90 CRI available.

**ELECTRICAL:** 120-277VAC 50/60Hz, constant current driver (<20% THD, >0.90 PF). Standard 0-10V Dimming with 1-100% range.

**FINISH:** White antimicrobial polyester powder coat finish following multi-stage iron phosphate pre-treatment. Fasteners are painted to match the housing.

**GASKET:** Closed cell EPDM and closed cell silicone gaskets air contaminants from entering the fixture.



**INSTALLATION:** Universal recessed mounting accommodates Grid and Flange installations. Luminaires will be supplied with adjustable swing arms that can be used for Flange applications or secured to the side of housing for Grid applications. Compatible with 1-1/2" and 15/16" Grid systems. Mounting for custom ceilings available, consult factory.

**WARRANTY:** 5 Year Warranty.




**LABEL:** Fixture is certified to UL standards by Intertek Testing Laboratory. Suitable for Wet Locations, IP65 Rated per IEC60598, Meets ISO Class 3 (Fed Std. 209E/ Class 10). IC-Rated per UL 1598. This product is Made in America and complies with the Buy American Act (BAA), and the Build America, Buy America Act (BABAA).

## DIMENSIONAL DATA

SCVR22-DC



SCVR24-DC



The DuraCare™ V Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse\*.

\*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
(773) 847-1400  
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

## PERFORMANCE DATA\*

\*LEDs are frequently updated therefore values may change without notice.

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
SCVR22-DC	L2 = Low	3500K	1975	79	25
		4000K	2075	83	25
		5000K	2200	88	25
	L4 = Medium	3500K	3850	77	50
		4000K	4050	81	50
		5000K	4250	85	50
	L6 = High	3500K	5880	84	75
		4000K	6230	89	75
		5000K	6650	95	75
SCVR24-DC	L2 = Low	3500K	4800	96	50
		4000K	5100	102	50
		5000K	5350	107	50
	L4 = Medium	3500K	9400	94	100
		4000K	9900	99	100
		5000K	10400	104	100
	L6 = High	3500K	14400	96	150
		4000K	15300	102	150
		5000K	16050	107	150

