# **STARSTEP** SERIES



PROJECT:
TYPE:
PRODUCT:
APPROVED BY:

## **PRODUCT FEATURES**

- Intended for Fall Prevention in healthcare settings, including Patient Rooms, Patient Bathrooms, Corridors, Lobbies, Waiting Rooms, Nurses' Stations, and more
- Faceplace constructed of durable cast zinc-magnesium and features integral embedded driver (5W max.)
- 3 Face plates styles: horizontal louver, horizontal hood and open frame with diffuse lens
- Available in 3000K White, Amber & Blue LED
- Certified to UL standards by Intertek Testing Laboratories for Wet Location. IP65 certified per IEC60598



SNL Series







### **ORDERING INFORMATION**

Example: SNL3-OF-L30-90C-12-W

SNL3		L		90C
Series	Faceplate	Source	Color Temp.	CRI
	OF = Open	L = LED	<b>30</b> = 3000K	<b>90C</b> = 90 CRI
	HL = Horizontal Louver		AMB = Amber	
	HH = Horizontal Hood		BLU = Blue	

Voltage	Finish	Options
<b>12</b> = 120V	<b>w</b> = White	HB = Hanger Bars
<b>27</b> = 277V	DB = Dark Bronze	<b>TH</b> = Tamper-resistant Torx® head fasteners
	BN = Brushed Nickel	

# **STARSTEP** SERIES



#### **SPECIFICATIONS**

**FACEPLATE:** Durable cast zinc-magnesium in three styles: horizontal hood, open frame with diffused opal lens, or horiztonal louver.

LENS: .125" White acrylic lens.

**LED:** Available in 3000K, Amber or Blue LED with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in a 25°C ambient temperature environment, compliant with IES LM-80 testing standards.

**ELECTRICAL:** 120VAC or 277VAC 50/60HZ integrated,embedded Driver Max @ 5 watt 3.6 watt normal.


**FINISH:** White or Dark Bronze antimicrobial polyester powder coat finish following multi-stage iron phosphate pretreatment on all exposed room-side painting surfaces, unless otherwise specified. Brushed Nickel is also available.


INSTALLATION: Recessed with Integral backbox.

WARRANTY: 5 Year Warranty.

**LABEL:** Certified to UL standards by Intertek Testing Laboratories for, IP65 certified per IEC60598.

#### **DIMENSIONAL DATA**











OPEN FRAME WITH DIFFUSED OPAL LENS

OPEN FRAME WITH HORIZONTAL LOUVER DIFFUSED OPAL LENS



HORIZONTAL LOUVER

